



oilfino Cultor UTTO Multitrac



DESCRIPTION

Hydraulic-Getriebe-Fluid UTTO.

FEATURES

oilfino Cultor UTTO Multitrac is a UTTO Universal Transmission Tractor Oil (transmission, hydraulics) for the supply of agricultural tractors and construction machinery with a common oil circuit for transmissions/axle drives and hydraulic systems and has been specially developed for use in hydrostatic transmissions and automatic CVT transmissions. Oilfino Cultor UTTO Multitrac is ideally suited for wet brakes in powershift clutches and power take-offs. High-quality base oils and selected additives ensure trouble-free operation of all units at any time of the year.

SPECIFICATIONS

- UTTO
- SAE-Klasse 10W-30
- SAE-Klasse 75W-85
- ISO VG 46 bis 68
- API GL-4

RECOMMENDATIONS

- AGCO Powerfluid 821 XL
- AGCO Q-186 (White farm)
- Allison C-4
- Case MS 1206, 1207, 1209, 1210, 1230
- Case New Holland CNHA MAT 3505, 3506, 3509, 3525, 3526
- Case New Holland CNHA MAT 3540, 3541
- Caterpillar TO-2
- Fendt FWN 81001
- Ford M2C 86 B/C, 134-D
- John Deere JDM J 20 C, J 20 D
- Komatsu KES 07.866, AOX, Dresser B06.002
- Kubota UDT, Kubota Super UDT2
- Massey Ferguson MF CMS M 1127 A/B, 1135, 1141, 1143, 1145
- New Holland FNHA 2-C-200.00, 201.00
- NH 410 B, 420 A
- Valtra G2-08, G2-A22
- Vickers / Eaton I-286-S, M 2950S
- Volvo WB 101
- ZF TE-ML 03E, 05F, 06K, 17E, 21F

NOTE

oilfino Cultor UTTO Multitrac complies with the regulations of well-known tractor manufacturers, especially for Fendt Vario transmissions. It meets the requirements of the UTTO specification FWN 81001 for use in AGCO Group vehicles (such as Fendt, Massey Ferguson, Valtra) and is suitable for Fendt tractors from generation 7 (2022). Oilfino Cultor UTTO Multitrac is backwards compatible for Fendt Group vehicles and can also be used in older Fendt vehicles. Due to its very good cold flow behaviour and the flat viscosity-temperature profile, oilfino Cultor UTTO Multitrac is an HVLP hydraulic oil of viscosity class ISO VG 46 to 68 that is ideally suited for hydraulic systems in construction machinery. The requirements of API GL-4 are exceeded and can also be used in manual transmissions of agricultural machinery.

Specific data	Method	Unit	oilfino Cultor UTTO Multitrac
SAE Class	SAE J 306 / J 300		75W-85 / 10W-30
Density at 15°C	DIN EN ISO 12 185	kg/m ³	0,864
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	64,1
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	11,4
Viscosity Index (VI)	DIN ISO 2909		175
Flash Point COC °C	DIN EN ISO 2592	°C	245
Pourpoint	DIN EN ISO 3016	°C	-45

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.