



oilfino Finoplex CA 2



DESCRIPTION

oilfino Finoplex CA 2 is a high-quality and modern high-performance product that is suitable for industrial, marine and off-road applications.

PROPERTIES

By producing oilfino Finoplex CA 2 with high-quality base oils and the latest generation of thickeners made from calcium sulfonate complex soap, oilfino Finoplex CA 2 has improved properties in terms of water resistance, load carrying capacity and corrosion protection. The remarkable high-pressure behaviour due to natural EP and anti-wear properties in combination with exceptionally good water resistance enable even with high water content, no loss of consistency and, due to the calcium sulfonate thickener used, very good corrosion protection properties in combination with seawater.

SPECIFICATIONS

- DIN 51502: KP2N 30
- ISO 12924: L XC(F)DIB2

Specific Data	Method	Unit	oilfino Linogas LA 40
NLGI Class	ASTM D 217		2
Condition			Soft, supple
Color			Brown
Thickener			Thickener Calcium Sulfonate Comple
Dropping point	IP 396	°C	>280
Base oil viscosity at 40°C	ASTM D 7152	mm ² /s	280
Base oil viscosity at 100°C	ASTM D 7152	mm ² /s	19
Walkpenetration	ISO 2137		265–295
Four-ball test, welding force	DIN 51350:4	N	6500
Water resistance	DIN51807:1		0
Water leaching at 79°C	ISO 11009	%	<5
SKF Emlcor Salt Water	ISO 11007	Korrosionsgrad	0–0
Use Temperature/Short Term		°C/°C	-30 to +140 / max +180

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.