



## PRODUCT INFORMATION

# oilfino Via Extra 5W-40



## DESCRIPTION

**oilfino Via Extra** is a synthetic high-performance smooth-running engine oil for petrol and diesel engines with and without turbocharging. State-of-the-art synthesis technology in conjunction with an extremely low cold viscosity and stable high-temperature viscosity ensures a significant fuel saving potential.

## PROPERTIES

oilfino Via Extra ensures wear protection and excellent oxidation stability through the selected combination of high-quality synthetic components and selected additives. The balanced additive ensures very good engine cleanliness and prevents the formation of black sludge.

## SPECIFICATIONS

- ACEA A3/B3-16, ACEA - A3/B4, API - CF, API - SN,
- API - SN Plus,
- API - SP

## RECOMMENDATIONS

- MB - 229.3
- PORSCHE - A40
- VW - 502 00
- VW - 505 00
- BMW - LONGLIFE-01
- FIAT - 9.55535-H2
- FIAT - 9.55535-M2
- FIAT - 9.55535-Z2
- MB - 226.5
- OPEL - GM-LL-A-025
- OPEL - GM-LL-B-025
- PSA - B71 2296
- RENAULT - RN 0700
- RENAULT - RN 0710

## FREIGABEN

- MB 229.3

| Specific Data      | Method       | Unit               | oilfino Linogas LA 40 |
|--------------------|--------------|--------------------|-----------------------|
| SAE Grade          | SAE J 300    |                    | 5W-40                 |
| Density at 15°C    | DIN 51757    | Kg/m <sup>3</sup>  | 856                   |
| Viscosity at 40°C  | DIN 51562    | mm <sup>2</sup> /s | 85,3                  |
| Viscosity at 100°C | DIN 51562    | mm <sup>2</sup> /s | 14.1                  |
| Viscosity index    | DIN ISO 2909 |                    | 171                   |
| Flash Point COC    | DIN ISO 2592 | °C                 | 236                   |
| Pour Point         | DIN ISO 3016 | °C                 | -42                   |
| Base Number        | DIN ISO 3771 | mgKOH/g            | 11.3                  |
| Sulphated Ash      | DIN 51575    | g/100g             | 1.2                   |

*All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.*