



PRODUCT INFORMATION

oilfino Via Ultra G 5W-30



DESCRIPTION

oilfino Via Ultra G is a synthetic high-performance long-life engine oil for modern petrol and diesel engines, including turbocharged engines and direct injectors. Synthetic components and selected additives ensure a high level of fuel savings and thus a reduction in emissions to protect the environment.

PROPERTIES

The very good pumping capacity in conjunction with a very low pump temperature limit ensures excellent cold start properties. High oil film stability reliably protects the engine from wear even at high temperatures and under extreme loads. Very low evaporation losses protect against oil consumption and reduce environmental pollution. Gentle on exhaust gas aftertreatment systems due to low sulphated ash, low phosphorus and sulphur content.

SPECIFICATIONS

- ACEA C2
- ACEA C3
- API SP
- API SN Plus

RECOMMENDATION

- BMW LONGLIFE-04
- FIAT 9.55535-S1
- FIAT 9.55535-S3
- FORD WSS-M2C917-A
- MB 229.31
- MB 229.51
- MB 229.52
- OPEL GM-LL-A-025
- OPEL GM-LL-B-025
- RENAULT RN 0700
- RENAULT RN 0710
- VW 505 00
- VW 505 01
- IVECO 18-1811 Classe SC1
- HYUNDAI
- KIA
- CHRYSLER MS 11106
- GM dexos 2
- OPEL OV 040 1547 - D30
- OPEL OV 040 1547 - G30

RELEASES

- BMW LONGLIFE-04
- MB 229.52

Specific data	Method	Unit	oilfino Via Ultra G 5W-30
SAE grade	DIN 51511		5W-30
Density at 15°C	DIN 51757	Kg/m ³	853
Viscosity at -30 °C	DIN 51398	mPAs	6150
Viscosity at 40 °C	DIN 51562	mm ² /s	68.6
Viscosity at 100 °C	DIN 51562	mm ² /s	11.9
Viscosity index	DIN ISO 2909		171
Flash point	DIN ISO 2592	°C	240
Pour Point	DIN ISO 3016	°C	-39
Base number	DIN ISO 3771	mgKOH/g	7.2
Sulphate ash	DIN 51575	g/100g	0.75

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.