

Page 1/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.10.2023 Version number 1.0 Revision: 25.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Oilfino Finocut Casting
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture

Lubricant

Metal-working product

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

oilfino Mineralöl GmbH

Werkstr. 12

D- 25497 Prisdorf

info@oilfino.com

Tel.: +49 (0) 4101 / 79900

www.oilfino.com

- · Further information obtainable from: product safety department
- · 1.4 Emergency telephone number:

Poison Information Centre North (Göttingen)

Phone +49 (0)551-19240

National Poisons Information Centre: +353 (1) 809 2166 (8.00 a.m. to 10.00 p.m. 7 days a week)

Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



Page 2/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.10.2023 Version number 1.0 Revision: 25.10.2023

Trade name: Oilfino Finocut Casting

· Hazard pictograms

(Contd. of page 1)



GHS07

- · Signal word Warning
- · Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P264 Wash thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear eye protection / face protection.
P302+P352 IF ON SKIN: Wash with plenty of water.
P321 Specific treatment (see on this label).

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse. P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

EUH 208: Contains 2-n-butyl-benzo[d]isothiazol-3-one. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description**: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



Page 3/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.10.2023 Version number 1.0 Revision: 25.10.2023

Trade name: Oilfino Finocut Casting

	(Contd. of page 2)
nenoxypropan-2-ol Irrit. 2, H319	≥0-<10%
ninoethanol n Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, 2; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT 3, H335; Aquatic Chronic 3, H412 cific concentration limit: TOT SE 3; H335: C ≥ 5%	≥2.5-<3%
clohexylamine te Tox. 3, H301; Acute Tox. 3, H311; Skin Corr. 1B, 4; Eye Dam. 1, H318; Aquatic Acute 1, H400; atic Chronic 1, H410	≥0.25-<1%
butyl-benzo[d]isothiazol-3-one i Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 400 (M=10); Aquatic Chronic 1, H410 (M=1); Skin s. 1, H317	≥0.1-<0.25%
	nenoxypropan-2-ol Irrit. 2, H319 minoethanol Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, 2; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT 3, H335; Aquatic Chronic 3, H412 cific concentration limit: TOT SE 3; H335: C ≥ 5% clohexylamine te Tox. 3, H301; Acute Tox. 3, H311; Skin Corr. 1B, 4; Eye Dam. 1, H318; Aquatic Acute 1, H400; atic Chronic 1, H410 butyl-benzo[d]isothiazol-3-one i Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 400 (M=10); Aquatic Chronic 1, H410 (M=1); Skin

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)



Page 4/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.10.2023 Version number 1.0 Revision: 25.10.2023

Trade name: Oilfino Finocut Casting

(Contd. of page 3)

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Use fire extinguishing methods suitable to surrounding conditions.

CO2, powder or water spray. Fight larger fires with water spray.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.

(Contd. on page 5)



Page 5/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.10.2023 Version number 1.0 Revision: 25.10.2023

Trade name: Oilfino Finocut Casting

(Contd. of page 4)

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Recommended storage temperature: 5-40°C
- · Storage class (TRGS): 10
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

141-43-5	2-aminoethanol		
Oral	DNEL Long-term - oral, systemic effects		3.75 mg/kg_bw/day (general public)
Dermal	DNEL Long-term – dermal, s	systemic effects	1 mg/kg_bw/d (Worker)
			0.24 mg/kg_bw/d (general public)
Inhalative	DNEL long-term - inhalation	local effects	2 mg/m³ (general public)
	DNEL Long-term – inhalation, systemic effects		3.3 mg/m³/d (Worker)
101-83-7	dicyclohexylamine		
Dermal	DNEL Long-term – dermal, s	systemic effects	0.1 mg/kg_bw/d (Worker)
Inhalative	DNEL Long-term – inhalation, systemic effects		0.353 mg/m³/d (Worker)
PNECs			
141-43-5	2-aminoethanol		
PNEC sho	ort term, fresh water	0.085 mg/l (Aquat	ic organisms)
PNEC sho	ort term, sea water	0.0085 mg/l (Aqua	atic organisms)
PNEC sho	ort term, sewage plant	100 mg/l (Aquatic	organisms)
PNEC sho	ort term fresh water sediment	0.434 mg/kg (Aqu	atic organisms)
PNEC sho	ort term soil	0.0367 mg/kg (ter	esstric organisms)
PNEC sho	ort term sea water sediment	0.0434 mg/kg (Aq	uatic organisms)
PNEC sho	ort term, intermittent releases	0.028 mg/l (Aquat	ic organisms)
101-83-7	dicyclohexylamine		
PNEC sho	ort term, fresh water	0.00032 mg/l (Aqu	uatic organisms)
PNFC sho	ort term, sea water	0.00003 mg/l (Aqu	uatic organisms)

GB



Page 6/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.10.2023 Version number 1.0 Revision: 25.10.2023

Trade name: Oilfino Finocut Casting

		(Contd. of page 5)
PNEC short term, sewage plant	108 mg/l (Aquatic organisms)	
PNEC short term fresh water sediment	0.00529 mg/kg (Aquatic organisms)	

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls

Use only in well-ventilated areas. In case of open handling, use devices with local exhaust ventilation if possible. If local exhaust ventilation is not possible or is insufficient, ensure good ventilation of the work area where possible. Technical measures and the use of appropriate work procedures take precedence over the use of personal protective equipment.

- Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Respiratory protection: Not required.
- Hand protection



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Material: NBR (nitrile rubber), CR (polychloroprene, chloroprene rubber),

Thickness of glove material: 0.70 mm

Penetration time (maximum wearing time): > 480 min

As protection from splashes gloves made of the following materials are suitable:

Material: NBR (nitrile rubber), CR (polychloroprene, chloroprene rubber),

Thickness of glove material: 0.40 mm

Penetration time (maximum wearing time): > 30 min

· Not suitable are gloves made of the following materials: PVA gloves

(Contd. on page 7)



Page 7/13

(Contd. of page 6)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.10.2023 Version number 1.0 Revision: 25.10.2023

Trade name: Oilfino Finocut Casting

· Eye/face protection

orotection

Tightly sealed goggles

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chemical properties

· General Information

Physical state
 Colour:
 Odour:
 Odour threshold:
 Melting point/freezing point:

Fluid

 Light yellow
 Characteristic
 Not determined.
 Undetermined.

· Boiling point or initial boiling point and

boiling range >100 °C
Flammability Not applicable.

Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: >100 °C

· **Decomposition temperature:** Not determined.

· pH at 20 °C 9.9

· Viscosity:

· Kinematic viscosity at 20 °C 115 mm²/s

Viscosity at 100°C:

• **Dynamic:** Not determined.

Solubility

• water: Fully miscible.

· Partition coefficient n-octanol/water (log

value) Not determined.
• Vapour pressure: Not determined.

· Density and/or relative density

Density at 20 °C: 0.987 g/cm³
 Relative density Not determined.
 Density (@15°C) Not determined.

(Contd. on page 8)



Page 8/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.10.2023 Version number 1.0 Revision: 25.10.2023

Trade name: Oilfino Finocut Casting

(Contd. of page 7)

· Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

· Ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Void

Void

· Solvent content:

· Organic solvents: 2-<4 % 2-<4 % · VOC (EC)

Change in condition

Pyrophoric solids

· Evaporation rate Not determined.

· Information with regard to physical hazard

classes Explosives

Void Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void

Self-heating substances and mixtures

· Substances and mixtures, which emit

flammable gases in contact with water Void · Oxidising liquids Void Oxidising solids Void · Organic peroxides Void

Corrosive to metals Void Desensitised explosives Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

(Contd. on page 9)



Page 9/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.10.2023 Version number 1.0 Revision: 25.10.2023

Trade name: Oilfino Finocut Casting

(Contd. of page 8)

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50	values relevant for classification:	
ATE (Acu	te Toxicity Estimates)	
Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>12,500-24,012 mg/kg (rabbit)
Inhalative	LD50	>367-1,100 mg/kg
141-43-5	2-aminoethanol	
Oral	LD50	2,050 mg/kg (rat)
Dermal	LD50	1,000 mg/kg (rabbit)
101-83-7	dicyclohexylamine	
Oral	LD50	200 mg/kg (rat)
	Acute Toxicity Estimate of ingredient (ATE) oral	200 mg/kg
Dermal	LD50	200-316 mg/kg (rabbit)
	Acute toxicity estimates	200 mg/kg
4299-07-4	2-n-butyl-benzo[d]isothiazol-3-one	
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.

(Contd. on page 10)



Page 10/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.10.2023 Version number 1.0 Revision: 25.10.2023

Trade name: Oilfino Finocut Casting

· 11.2 Information on other hazards

(Contd. of page 9)

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:	
101-83-7 dicycloh	exylamine
LC50 (96h)	12 mg/l (Fish)
EC50 (48h)	1.5 mg/l (daphnia)
4299-07-4 2-n-but	yl-benzo[d]isothiazol-3-one
LC50 (96h) mg/ltr.	0.15 mg/ltr (rainbow trout)
EC50 (48h)	0.093 mg/l (daphnia)
40.00	

12.2 Persistence and degradability

102-71-6 Triethanolamine >87 %

· 12.3 Bioaccumulative potential

4299-07-4 2-n-butyl-benzo[d]isothiazol-3-one 2,86

- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects No further relevant information available.
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Self-classification according to Annex 1 (to § 4 paragraph 1, § 8 paragraph 1 and § 10 paragraph 2) of the Ordinance on Facilities for Handling Substances Hazardous to Water 1, 2 (AwSV).

(Contd. on page 11)



Page 11/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.10.2023 Version number 1.0 Revision: 25.10.2023

Trade name: Oilfino Finocut Casting

Harmful to aquatic organisms

(Contd. of page 10)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information	tion	
· 14.1 UN number or ID number · ADR, IMDG, IATA	not regulated	
· 14.2 UN proper shipping name · ADR, IMDG, IATA	not regulated	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	not regulated	
· 14.4 Packing group · ADR, IMDG, IATA	not regulated	
· 14.5 Environmental hazards:	Not applicable.	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Maritime transport in bulk accordi IMO instruments	ing to Not applicable.	
· UN "Model Regulation":	not regulated	

- GB



Page 12/13

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.10.2023 Version number 1.0 Revision: 25.10.2023

Trade name: Oilfino Finocut Casting

(Contd. of page 11)

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: (Substances not listed)

None of the ingredients is listed.

- Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- National regulations:
- VOC (EU) 19.7-<39.5 g/l
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

· Disclaimer

This safety data sheet contains only safety relevant information. The information is based on the state of our knowledge at the time of revision, however, it does not constitute a guarantee of product properties, product information or product specifications and does not establish a contractual legal relationship. This document is only valid in its unchanged form. In the event of changes by third parties, the exhibitor accepts no responsibility for form and content or for any damages or claims arising from such changes. The information is not transferable to other products. If the product named in this safety data sheet is mixed, blended or processed with other materials or is subjected to processing, the information in this safety data sheet cannot be transferred to the new material produced in this way, unless expressly stated otherwise. The data sheet does not release the user from the obligation to ensure that he acts in accordance with all regulations in connection with his activity.

· Relevant phrases

H301 Toxic if swallowed.

(Contd. on page 13)



Page 13/13

(Contd. of page 12)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.10.2023 Version number 1.0 Revision: 25.10.2023

Trade name: Oilfino Finocut Casting

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Contact: MSDS authorized Person

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

GB