

oilfino Brake Fluid DOT4



DESCRIPTION

oilfino Brake Fluid DOT4 is a synthetic brake fluid with a steam bubble reducing, very high dry and wet boiling point which provides excellent protection against corrosion and wear for all metal parts. oilfino Brake Fluid DOT4 significantly reduces foam formation and is compatible with all seals and hoses used in the brake system.

AREAS OF APPLICATION

oilfino Brake Fluid DOT4 is used in brake and clutch systems of vehicles for which a synthetic brake fluid according to DOT4 is recommended or prescribed. It is mixable with all synthetic brake fluids of the **same quality**.

SPECIAL NOTES

- Storage of brake fluid closed in its original packaging only.
- Brake fluid may cause damage to the varnishing.

PERFORMANCE LEVEL

- FMVSS 116 DOT4
- SAE J 1703 F
- ISO 4925

Specific Data	Method	Unit	oilfino Brake Fluid DOT4
Density at 15°C	DIN 51757	g/cm ³	1,060
Viscosity at -40°C	DIN ISO 3104	mm ² /s	<1350
Dry boiling point (/min)	DIN ISO 4925	°C	>260
Wet boiling point (/min)	DIN ISO 4925	°C	>155

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.