

oilfino Duo Extreme



DESCRIPTION

oilfino Duo Extreme is a fully synthetic 2-stroke engine oil specially developed for high loads in karting, street and off-road races. It is intended to be used in heavy duty engines with air or water cooling, premixed or in direct injection systems with oil/petrol mixtures, depending on the mixing ratio specified by the manufacturer.

PROPERTIES

The low-ash and 100% synthetic formulation with excellent temperature stability prevents formation of deposits and thus also backfire or pre-ignition caused by deposits.

Additional benefits:

- Prevents moving parts from jamming and exhaust system blocking
- Excellent lubrication and wear protection of bearings and cylinders
- Excellent protection from rust and corrosion
- Very good temperature behaviour
- Self-mixing with oil injection systems or premixture

SPECIFICATION

- ISO-L-EGD
- API TC

PERFORMANCE LEVEL

- Jaso FD
- TISI
- Husqvarna Chainsaw
- Piaggio
- Rotax Snowmobile

Specific Data	Method	Unit	oilfino Duo Extreme
Density at 15°C	D 1298	kg/m ³	894
Kin. Viscosity at 40°C	D 445	mm ² /s	56,8
Kin. Viscosity at 100°C	D 445	mm ² /s	9,1
Viscosity index	D 2270		137
Sulphate ash	D 874	% mass	0,18
Flash point	D 93	°C	115
Pour point	D 97	°C	-45

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.