

# oilfino Duo Super



## DESCRIPTION

**oilfino Duo Super** is a semi-synthetic 2-stroke engine oil specially developed for high temperature ranges and heavy loads. It is intended to be used in heavy duty engines with air or water cooling, premixed or in direct injection systems with oil/petrol mixtures. E.g.: Motorcycles, mopeds, scooters, snow scooters or chainsaws.

## PROPERTIES

Excellent lubrication of bearings due to special formulation for oilfino Duo Super leads to increasing load capacity and extending service life, e.g. it prevents the piston rings from seizing and reduces jamming of the exhaust system.

Additional benefits:

- No formation of smoke when either starting or driving
- Reduces backfire and preignition which could be caused by deposits
- Excellent protection from rust and corrosion
- Good flowability at low temperatures
- Self-mixing with oil injection systems or premixture

## SPECIFICATION

- API TC
- ISO-L-EGD

## PERFORMANCE LEVEL

- JASO FD
- Husqvarna 272
- Global GD
- 2-Stroke DFI

Specific Data	Method	Unit	oilfino Duo Super
Density at 15°C	D 1298	kg/m <sup>3</sup>	872
Kin. Viscosity at 40°C	D 445	mm <sup>2</sup> /s	67,7
Kin. Viscosity at 100°C	D 445	mm <sup>2</sup> /s	9,5
Viscosity index	D 2270		121
Sulphate ash	D 874	% mass	0,05
Flash point	D 93	°C	123
Pour point	D 97	°C	-33

*Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.*