

oilfino Econ 5000 15W-40



DESCRIPTION

oilfino Econ 5000 is a multigrade engine oil for diesel and petrol engines with or without turbocharging. It offers reliable cold start performance throughout the year and its shear-stable components ensure high temperature resistance for the entire oil retention period. oilfino Econ T 5000 was developed for the universal supply of mixed fleets.

PROPERTIES

oilfino Econ T 5000 ensures wear protection and excellent engine cleanliness by selectively combining high-quality base oils and additives. Great protection against bore polishing helps to avoid excessive oil consumption and the excellent cleaning and sludge carrying capacity prevents formation of black sludge.

SPECIFICATION

- ACEA A2/B2
- ACEA E2
- API SJ/CF-4

PERFORMANCE LEVEL

- MB 228.1/229.1
- MTU Typ 1
- MAN 271
- Allison C-4
- Volvo VDS

Specific Data	Method	Unit	oilfino Econ 5000 15W-40
SAE grade	DIN 51511		15W-40
Density at 15°C	DIN 51757	kg/m ³	882
Viscosity at 40°C	DIN 51562	mm ² /s	105
Viscosity at 100°C	DIN 51562	mm ² /s	14,0
Viscosity index	DIN ISO 2909		133
Flash point	DIN ISO 2592	°C	230
Pour point	DIN ISO 3016	°C	-33
Base number	DIN ISO 3771	mgKOH/g	8,9
Sulphate ash	DIN 51575	g/100g	1,1

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.