

oilfino Sponte ATF A



DESCRIPTION

Transmission oil for automatic transmissions according to GM specification ATF type A suffix A as well as power steering, fluid couplings and hydraulics in passenger cars, trucks, buses and construction vehicles.

PROPERTIES

High level of shifting comfort results from matching it to friction linings used in the transmission. oilfino ATF A offers very high wear protection in the gearbox due to its excellent oxidation stability and precisely defined constant friction performance. Due to different requirements on friction coefficients for automatic transmission oils, instructions from manufacturers must be followed.

PERFORMANCE LEVEL

- Typ Suffix A
- MB 236.2
- MAN 339 Typ A
- Renk Doromat
- Allison C-3

Specific Data	Method	Unit	oilfino Sponte ATF A
Colour			Red
Density at 15°C	DIN 51757	kg/m ³	866
Kinematic viscosity at 40°C	D 445	mm ² /s	34,1
Kinematic viscosity at 100°C	D 445	mm ² /s	7,3
Viscosity index	D 2270		182
Flash point	D 92	°C	208
Pour point	D 97	°C	-45
Dynamic viscosity at -40°C	DIN 51398	mPa.s	42.600

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.