

oilfino Sponte ATF III



DESCRIPTION

Transmission oil for automatic transmissions according to the current GM specification Dexron III H as well as power steering, fluid couplings and hydraulics in passenger cars, trucks, buses and construction vehicles.

PROPERTIES

High level of shifting comfort results from matching it to friction linings used in the transmission. oilfino Sponte ATF III offers very high wear protection in the gearbox due to its excellent oxidation stability and precisely defined constant friction performance. Due to different requirements on friction coefficients for automatic transmission oils, instructions from manufacturers must be followed.

PERFORMANCE LEVEL

- GM Dexron III-H
- Allison C4, TES-389
- MAN 339 Typ Z-2
- MB 236.1, 236.6, 236.9, 236.10
- ZF TE-ML 04D, 05L, 14B, 16L, 17C
- VOLVO 1161521/1161511
- VOLVO Transmission Oil 97341
- VOITH H 55.6336.3x Extended Drain (G1363)

Specific Data	Method	Unit	oilfino Sponte ATF III
Colour			Red
Density at 15°C	DIN 51757	kg/m ³	860
Kinematic viscosity at 40°C	DIN 51562	mm ² /s	35,7
Kinematic viscosity at 100°C	DIN 51562	mm ² /s	7,4
Viscosity index	D 2270		180
Flash point	DIN ISO 2592	°C	216
Pour point	DIN ISO 3016	°C	<-50

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.