

oilfino Varius G 300



DESCRIPTION

Multi-purpose gear oils with EP additives for use in manual, transfer and steering gears of commercial vehicles and passenger cars as well as in hypoid gears with small axle offset.

PROPERTIES

oilfino Varius G 300 offers excellent wear protection and optimised shifting capability even during extreme operations under most difficult conditions. Selected base oils combined with appropriate additive technology ensure very good flowability at low temperatures and great lubrication at high operating temperatures.

SPECIFICATIONS

- API GL-4
- MB 235.1
- ZF TE-ML 16A, 17A, 19A

Specific Data	Method	Unit	oilfino Varius G 300	
SAE grade	DIN 51512		80W	80W-90
Density at 15°C	DIN 51757	kg/m ³	897	891
Kinematic viscosity at 40°C	DIN 51562	mm ² /s	114	141
Kinematic viscosity at 100°C	DIN 51562	mm ² /s	11,9	14
Viscosity index	D 2270		92	99
Flash point	DIN ISO 2592	°C	220	224
Pour point	DIN ISO 3016	°C	-30	-27
VEH test A/8.3/90	DIN 51354		>12	>12

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.