

oilfino Varius G 500



DESCRIPTION

oilfino Varius G 500 are high-quality hypoid gear oils for highly stressed hypoid toothed drive axles of passenger cars and commercial vehicles.

PROPERTIES

oilfino Varius G 500 offers excellent wear protection and excellent oxidation and temperature stability even during extreme operations under most difficult conditions. Selected base oils combined with appropriate additive technology ensure very good flowability at low temperatures and great lubrication at high operating temperatures.

SPECIFICATION

- API GL-5

APPROVAL

- ZF TE-ML 16B, 17B, 19B, 21A (only SAE 80W90)

PERFORMANCE LEVEL

- MIL-L-2105 D
- MAN 342 Typ M2
- ZF TE-ML 05A, 12E (only SAE 80W90)
- ZF TE-ML 05A, 12E, 16C, 17B, 19B, 21A (only SAE 90)
- ZF TE-ML 05A, 12E, 16D, 21A (only SAE 85W140)
- Scania STO 1:0 (only SAE 85W140)
- Volvo 97310 (only SAE 85W140)
- Mack GO-G (only SAE 85W140)
- GM (only SAE 85W140)
- Ford M2C-9002A (only SAE 85W140)
- DAF (only SAE 85W140)
- CS 3000B (only SAE 85W140)

Specific Data	Method	Unit	oilfino Varius G 500		
SAE grade	SAE J 306		80W-90	90	85W-140
Density at 15°C	DIN 51757	kg/m ³	892	902	906
Kinematic viscosity at 40°C	DIN 51398	mm ² /s	140	198	337
Kinematic viscosity at 100°C	DIN 51398	mm ² /s	14,1	17,6	24,2
Viscosity index	D 2270		98	95	96
Flash point	DIN ISO 2592	°C	230	216	220
Pour point	DIN ISO 3016	°C	-33	-24	-21
VEH test A/8.3/90	DIN ISO 14635		>12	>12	>12

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.