

oilfino Varius G 600



DESCRIPTION

oilfino Varius G 600 is a synthetic low friction gear oil for heavy-duty manual transmissions, to be used in commercial vehicles and passenger cars under extreme mechanical and thermal loads. Particularly suitable when using carbon- and molybdenum-coated synchroniser rings of ZF transmissions. The use of synthetic base oils and additives matched to them exceeds current requirements.

PROPERTIES

oilfino Varius G 600 offers excellent wear protection and excellent oxidation and temperature stability even during extreme operations under most difficult conditions. Selected base oils combined with appropriate additive technology ensure very good flowability at low temperatures and great lubrication at high operating temperatures. Using oilfino Varius G 600 results in reduced maintenance costs and increasing efficiency due to extended oil change intervals according to manufacturer specifications.

SPECIFICATION

- API GL-4

PERFORMANCE LEVEL

- MAN 341 Typ E3/Z4
- Volvo 97305
- ZF TE-ML 01L, 02L, 16K

Specific Data	Method	Unit	oilfino Varius G 600
SAE grade	SAE J 306		75W-80
Density at 15°C	DIN 51757	kg/m ³	858
Kinematic viscosity at 40°C	D 445	mm ² /s	57,7
Kinematic viscosity at 100°C	D 445	mm ² /s	9,6
Viscosity index	D 2270		150
Flash point	D 93	°C	240
Pour point	D 97	°C	-41

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.