

# oilfino Varius G 650



## BESCHREIBUNG

**oilfino Varius G 650** is a synthetic low friction gear oil for heavy-duty axle and transfer transmissions, to be used in commercial vehicles and passenger cars under extreme mechanical and thermal loads. The use of synthetic base oils and additives matched to them exceeds current requirements.

## PROPERTIES

oilfino Varius G 650 offers excellent wear protection and excellent oxidation and temperature stability even during extreme operations under most difficult conditions. Selected base oils combined with appropriate additive technology ensure very good flowability at low temperatures and great lubrication at high operating temperatures. Using oilfino Varius G 650 results in reduced maintenance costs and increasing efficiency due to extended oil change intervals according to manufacturer specifications.

## SPECIFICATIONS

- API GL-5

## PERFORMANCE LEVEL

- MB 235.8
- MAN Typ 342 S-1
- Volvo Transmission Oil 97312
- DAF
- Scania STO 1:0
- Mack GO-J
- ZF TE-ML 12B, 16F, 17B

Specific Data	Method	Unit	oilfino Varius G 650
SAE grade	SAE J 306		75W-90
Density at 15°C	DIN 51757	kg/m <sup>3</sup>	866
Kinematic viscosity at 40°C	D 445	mm <sup>2</sup> /s	100,8
Kinematic viscosity at 100°C	D 445	mm <sup>2</sup> /s	14,9
Viscosity index	D 2270		156
Flash point	D 93	°C	190
Pour point	D 97	°C	-51

*Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.*