

oilfino Via Eco Plus 5W-40



DESCRIPTION

A universal synthetic motor oil, developed according the most recent technology and based on specially selected synthetic base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained:

- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- reduced formation of combustion ashes
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

APPLICATION

This fuel economy motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below

PERFORMANCE LEVEL

- ACEA C3
- API SN, API SN Plus

Meets the requirements of:

- BMW Longlife-04
- MB 229.51, 229.31, 229.52
- VW 505.00/505.01

Specific Data	Method	Unit	oilfino Via Eco Plus 5W-40
Density at 15 °C		kg/l	0,850
Viscosity 40 °C		mm ² /s	75,80
Viscosity 100 °C		mm ² /s	13,20
Viscosity Index			180
Flash Point COC		°C	220
Pour Point		°C	-36
Total Base Number		mgKOH/g	7,0
Sulphate Ash		%	0,75

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.