

oilfino Via Eco V 0W-20



DESCRIPTION

oilfino Via Eco V 0W-20 is a synthetic fuel-efficient high-performance engine oil that has been developed to meet technical requirements of the new Volvo Drive-E engines with strong focus on fuel savings and reduction of CO₂ emissions. oilfino Via Eco GF 0W-20 is appropriate for usage throughout the year even at very low temperature and an ideal solution for downsizing engines with automatic start/stop.

PROPERTIES

- fuel savings of 3.4% proven in ACEA test M111FE
- exceptional flowability at very low temperatures - safe cold start
- High-quality additive package keeps engines clean under all conditions
- ensures compliance with EURO standards concerning pollutant load
- better protection of the TWC (three way catalytic converter) by optimised formulation

SPECIFICATIONS

- ACEA C5
- API SN

PERFORMANCE LEVEL

- ILSAC GF-5
- Volvo VCC RBS0-2AE

Specific Data	Method	Unit	oilfino Via Eco V 0W-20
SAE grade	SAE J 300		0W-20
Density at 15°C	D 4052	kg/m ³	845
Viscosity at 40°C	DIN 51562	mm ² /s	44,0
Viscosity at 100°C	DIN 51562	mm ² /s	8,6
Viscosity index	DIN ISO 2909		179
Flash point	DIN ISO 2592	°C	238
Pour point	DIN ISO 3016	°C	-48
Base number	ASTM D 2896	mgKOH/g	7,9
Sulphate ash	DIN 51575	g/100g	0,76

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.