

oilfino Via Optimus 0W-40



DESCRIPTION

oilfino Via Optimus 0W-40 is a fully synthetic high-performance low friction engine oil which ensures extreme wear protection, protection against deposits and black sludge as well as engine cleanliness. Extreme usage and high temperatures as well as quick oil penetration during cold starts are easily managed with the viscosity 0W-40. oilfino Via Optimus 0W-40 can be used throughout the year, even at very low temperature. With great fuel savings it contributes to a reduction in emissions which has positive impact on the environment.

PROPERTIES

- fuel savings up to 10% in the cold start phase
- exceptional flowability at very low temperatures - safe cold start
- high-quality additive package keeps the engine clean under all conditions
- ensures compliance with EURO standards concerning pollutant load
- better protection of the TWC (three way catalytic converter) due to optimised formulation

SPECIFICATIONS

- ACEA A3/B4
- API SN/CF

PERFORMANCE LEVEL

- MB 229.5/226.5
- Porsche A40
- Renault RN0700/0710
- VW 502.00/505.00
- BMW Longlife-01
- Ford WSS-M2C937-A
- Fiat 9.55535-M2/Z2
- PSA B71 2296

Specific Data	Method	Unit	oilfino Via Optimus 0W-40
SAE grade	SAE J 300		0W-40
Density at 15°C	DIN 51757	kg/m ³	844
Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	77,2
Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	13,6
Viscosity index	DIN ISO 2909		181
Flash point	DIN ISO 2592	°C	236
Pour point	DIN ISO 3016	°C	-54
Base number	DIN ISO 3771		10,2
Sulphate ash	DIN 51575	g/100g	1,1

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.