

oilfino Via Ultra G 5W-30



DESCRIPTION

oilfino Via Ultra G is a synthetic high-performance long-life engine oil for modern petrol and diesel engines, including turbo and direct injection engines. Synthetic components and selected additives ensure high fuel savings and thus a reduction in emissions to protect the environment.

PROPERTIES

Very good pumpability combined with a very low minimum pump temperature ensures excellent cold start properties. A high oil film stability provides protection from wear for the engine, even at high temperature and extreme loads. Due to very low evaporation losses oil consumption as well as negative environmental impact can be reduced. Exhaust gas aftertreatment systems are protected due to low sulphate ash, low phosphorus and sulphur content.

SPECIFICATIONS

- ACEA C3
- API SN/CF

PERFORMANCE LEVEL

- BMW Longlife-04
- GM dexos 2
- MB 229.51/229.31
- VW 502.00/505.01
- Renault RN 0700/0710
- Porsche A40

Specific Data	Method	Unit	oilfino Via Ultra G 5W-30
SAE grade	DIN 51511		5W-30
Density at 15°C	DIN 51757	Kg/m ³	853
Viscosity at -30°C	DIN 51398	mPAs	6150
Viscosity at 40°C	DIN 51562	mm ² /s	68,6
Viscosity at 100°C	DIN 51562	mm ² /s	11,9
Viscosity index	DIN ISO 2909		171
Flash point	DIN ISO 2592	°C	240
Pour point	DIN ISO 3016	°C	-39
Base number	DIN ISO 3771	mgKOH/g	7,2
Sulphate ash	DIN 51575	g/100g	0,75

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.