

oilfino Via Ultra V 0W-30



DESCRIPTION

Oilfino Via Ultra V is a fully synthetic low friction engine oil for use throughout the year. Using this engine oil results in fuel savings and extended oil change intervals for modern petrol and diesel engines. For latest Volvo engines it is necessary that the oil perfectly meets the strict requirements according to ACEA A5/B5. This standard is also recommended for various Renault, Citroen and Honda engines.

PROPERTIES

In addition to extended oil change intervals, oilfino Via Ultra V 0W-30 offers the following advantages:

- measurable fuel savings (approx. 2.6% according to ACEA M111FE)
- compatible with catalytic converters
- very high oxidation stability
- low evaporation losses
- high oil film stability under all loads
- excellent engine protection even at cold start
- very good protection against formation of foam
- above-average protection from rust and corrosion

SPECIFICATIONS

- ACEA A5/B5
- API SL/CF

PERFORMANCE LEVEL

- VOLVO VCC 95200377
- Ford WSS-M2C920-A
- Renault RN0700/0710

Specific Data	Method	Unit	oilfino Via Ultra V 0W-30
SAE grade	DIN 51511		0W-30
Density at 15°C	DIN 51757	kg/m ³	843
Viscosity at 40°C	DIN 51562	mm ² /s	54,2
Viscosity at 100°C	DIN 51562	mm ² /s	10,2
Viscosity index	DIN ISO 2909		180
TBN		mgKOH/g	9,7

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.