

## oilfino DRIVE LINE M 5W30



## DESCRIPTION

Oilfino Drive Line M SAE 5W30 is a synthetic high-performance low friction engine oil for modern passenger car engines. State-of-the-art synthetic technology combined with extremely low cold viscosity and stable high-temperature viscosity ensures significant fuel saving potential. Synthetic base oils with their innovative additive technology and reduced sulphate ash weight ensure compliance with current requirements and keep the effectiveness of the exhaust purification systems at extended run time.

## PROPERTIES

With its low-emission formulation, oilfino Via Special ensures performing exhaust systems of diesel engines for a very long time and the low sulphur and phosphorus content reduces the load on catalytic converters in petrol engines. Due to very low evaporation losses oil consumption as well as negative environmental impact can be reduced. Very good pumpability, even at low temperature, ensures best lubrication in the cold running phase. The excellent HTHS (High Temperature High Share) viscosity ensures safe operation of the engine even under extreme loads and high temperature.

## SPECIFICATIONS

- API SN
- ACEA C2, C3

## PERFORMANCE LEVEL

- MB 229.52/229.51
- BMW Longlife-04
- GM dexos 2
- VW 505.01
- Porsche C30

Specific Data	Method	Unit	oilfino DRIVE LINE M 5W30
SAE grade	DIN 51511		5W-30
Density at 15 °C	DIN 51757	kg/m <sup>3</sup>	848
Viscosity at 40°C	DIN 51562	mm <sup>2</sup> /s	72,8
Viscosity at 100°C	DIN 51562	mm <sup>2</sup> /s	12,4
Viscosity index	DIN 2909		169
Pour point	DIN 3016	°C	-35
Flash point	DIN 2592	°C	230

*Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.*