

oilfino Guard Fill - Diesel



PRODUCT PROPERTIES

oilfino Guard Fill Diesel keeps valves, injectors and combustion chambers free of carbonisation, reduces friction inside the engine and protects all metal surfaces from corrosion. The special combination of highly effective additives in the Guard Fill Diesel can reduce fuel consumption by up to 3% and emissions by up to 35% and is gentle to all materials in the engine and the diesel fuel system. Dampness and condensation will be removed and the upper cylinder area is well lubricated and protected. Guard-Fill keeps the engine in good condition during its entire life

AREA OF APPLICATION

For use in diesel powered engines. Recommended for engines with particle filter, turbo and catalytic converter.

APPLICATION

Fill directly into the diesel tank.

CONSUMPTION

75ml sufficient for 80 liters diesel. Mixing ratio: 1:1000

REACTION TIME

while engine is running

Specific Data	Method	Unit	oilfino Guard Fill - Diesel
Physical state			liquid
Colour			clear/colourless
Odour			aromatic
Initial boiling point and boiling range		°C	200 - 210
Flashpoint		°C	62
Density at 68 °F		Vol.-%	0,6
Water resistant		g/cm ³	83 - 0.87

Available Size	PU
75ml.	24
1000ml.	12

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.