

oilfino Truck Line 110 15W40



DESCRIPTION

Oilfino Truck Line 110 SAE 15W40 is a Super High Performance Diesel (SHPD) engine oil for heavily used engines, mechanically as well as thermally, with and without turbocharging. It offers reliable cold start performance at low outside temperature and assured lubrication at high operating temperatures. Selectively chosen additives secure usage at extended oil change intervals and reduce maintenance costs. It is designed with low sulphate ash, phosphorus and sulphur content (low SAPS) for Euro 5 diesel engines with diesel particulate filter (DPF) or catalytic converters (SCR). Usage with low-sulphur diesel (50 ppm or lower) and under heavy conditions.

PROPERTIES

Oilfino Truck Line 110 SAE 15W40 ensures wear protection and excellent engine cleanliness by selectively combining high-quality base oils and additives. Great protection against bore polishing helps to avoid excessive oil consumption and the excellent cleaning and sludge carrying capacity prevents formation of black sludge. Due to excellent oxidation and temperature stability safe operation even under extreme conditions and extended oil change intervals according to manufacturer specifications are provided. Vehicle and engine manufacturers without common approval process recommend engine oils of this performance category for extended oil retention periods in turbo diesel engines.

SPECIFICATIONS

- API CK-4/SN
- ACEA E9

PERFORMANCE LEVEL

- MB 228.31
- MAN M 3775
- Cat ECF-3
- Cummins CES 20086
- Detroit Diesel 93K222
- Deutz DQC III-18 LA
- Mack EOS-4.5
- MTU Typ 2.1
- Renault VI RLD-3
- Volvo VDS 4.5

Specific Data	Method	Unit	oilfino Truck Line 110 SAE 15W40
SAE grade	DIN 51511		15W-40
Density at 15°C	DIN 51757	kg/m ³	867
Viscosity at 40°C	DIN 51562	mm ² /s	93,10
Viscosity at 100°C	DIN 51562	mm ² /s	13,6
Viscosity index	DIN 2909		148
Pour point	DIN 3016	°C	-36
Flash point	DIN 2592	°C	236
Basenzahl	DIN 3371	mgKOH/g	8,1

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.