

# oilfino Truck Line Monogrades



## DESCRIPTION

**oilfino Truck Line Monogrades** are universal engine oil produced with high quality solvent refined base oils and a well-balanced choice of additives. Oilfino Truck Line Monogrades are suitable for gasoline and diesel engines, with or without supercharging.

## PROPERTIES

- an excellent detergency preventing from deposits in the hot zones of the engine
- a very active dispersion, that prevents from precipitation and sludge
- a powerful action against wear, corrosion and foam
- low ash contents

## SPECIFICATIONS

- API CF/SG
- ACEA E2

## PERFORMANCE LEVEL

- MB 228.0
- MTU Typ 1
- MAN 270
- ZF TE-ML 04B
- Caterpillar TO-2
- Allison C-4
- Renk Doromat \*nur 10W

Specific Data	Method	Unit	SAE 10W	SAE 20W20	SAE 30	SAE 40	SAE 50
SAE grade	DIN 51511		10W	20W-20	30	40	50
Density at 15°C	DIN 51757	kg/m <sup>3</sup>	882	864	891	898	900
Viscosity at 40°C	DIN 51562	mm <sup>2</sup> /s	37	54,6	97,4	148,8	206
Viscosity at 100°C	DIN 51562	mm <sup>2</sup> /s	6,1	8,09	10,8	15,1	19,4
Viscosity index	DIN 2909		111	117	107	102	107
Pour point	DIN 3016	°C	-39	-30	-24	-15	255
Flash point	DIN 2592	°C	224	215	230	244	-15
Base number	DIN 3371	mgKOH/g	11,6	6,9	6,9	6,9	6,9
Sulfate ash content	DIN 51575	%	1,6	0,91	0,91	0,91	0,91

*Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.*