

oilfino Ventus 32 - 68



DESCRIPTION

oilfino Ventus are compressor oils based on hydrocrack mineral oil with a special additive for oil-cooled screw compressors for particularly long change intervals

PROPERTIES

- good protection against deposits
- Good separation of oil / air and oil / condensed water
- good wear and corrosion protection behavior
- Use of Ventus enables production costs to be reduced
- Optimized compressor efficiency through extended downtimes
- Extension of the oil change intervals up to 4,000 operating hours for oil-cooled screw compressors
- Extend the life of the coalescence filter
- Good protection against dirt and high effectiveness of the filter over a long period

SPECIFICATIONS

- ISO DP 6521
- DIN 51 506 VDL
- ISO 6743-3A DAJ (for high loads)

Specific Data	Method	Unit	Ventus 32	Ventus 46	Ventus 68
Density at 15°C	ASTM D 1298	kg/m ³	841	850	862
Viscosity at 40°C	ASTM D 445	mm ² /s	32	46	68
Viscosityindex	ASTM D 4741		127	127	127
Pour point	ASTM D 97	°C	-33	-30	-33
Flash point	ASTM D 92	°C	238	244	254
Conradson	NFT 60116	%	0,10	0,10	0,10

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.