

oilfino Via Classic



DESCRIPTION

oilfino Via Classic products are specially alloyed engine oils for standard vehicles, with oil filter and closed crankcase ventilation systems. The oilfino Classic series is particularly designed to meet the special requirements of classic engines and the properties of older vehicles.

The customised lubricant technology protects the engine against black sludge and wear. Using oilfino Classic engine oils has positive impact on the service life of engines in classic vehicles. For the selection of the right viscosity, please contact your specialist.

SPECIFICATION

- ACEA CCMC G4
- API SF/CF

PERFORMANCE LEVEL

- MIL-L-2104 D
- MIL-L-46152 B
- MB 228.0

Specific Data	Method	Unit	oilfino Via Classic				
SAE grade	DIN 51511		20W-20	20W-50	30	40	50
Density at 15°C	D 4052	kg/m ³	888	891	891	897	902
Viscosity at 40°C	DIN 51562	mm ² /s	70	171,8	106	166	239
Viscosity at 100°C	DIN 51562	mm ² /s	9	18,9	11,7	15,6	19,6
Viscosity index	DIN ISO 2909		103	124	99	95	93
Flash point	DIN ISO 2592	°C	245	>200	264	279	290
Pour point	DIN ISO 3016	°C	-30	-18	-24	-24	-24
Base number	DIN ISO 3771	mgKOH/g	11,6	8,5	11,6	11,6	11,6
Sulphate ash	DIN 51575	g/100g	1,8	1,41	1,8	1,8	1,8

Information are provided to the best of our knowledge; no responsibility is taken for information accuracy. Technical data contain average values and are subject to accepted production variations. Due to continual product research and development, the information contained herein are subject to changes without notification.